



HIBRA02

The pictures shown are for illustrative purposes only. For shape, material and color specifications refer to internal descriptions.

Hibra 02

Technical data

INSTALL: Indoor and Outdoor

ACCESSIBILITY



Timeless




Tool-free openable fixture.
Replaceable internal components
without the need of tools.

OPTICAL TECHNOLOGY



Reflexa

Refracting optical system consist of
single-chip LED, aluminium reflector
extra-pure with silver PDV treatment
and extra clear tempered glass.



Scale: 1:10

Max. weight


HI2: : 8,8 lb (4 Kg)

EPA (CX5)


Plan: 0,9 ft² (0,084 m²)

FIXING TYPE


Ceiling support




Busbar



Steel cables



Loop



Infographic related to the Hibra family and not to the single product

STANDARD

Compliance: UL Standard 1598-CSA C22,2no.250.0.

CONFORMITY | PROTECTION

Conformity



Salt spray test

ISO 9227



8000 hr

Safety classes



Class I

Protection classes



Photobiological safety



Classe 0 Exempt
group IEC/TR62471

PLUS



DARK SKY
FRIENDLY



OPTICAL
FLEXIBILITY



LOW GLARE



SEPARATE UNITS
(ELECTRICAL AND
OPTICAL)

LIGHTING FIXTURE FEATURES

General features

| | |
|-------------------------------|--|
| Power source: | 120-277V 50/60Hz tolerance +/-10% |
| Current supply: | 350 mA 525 mA 700 mA 1050 mA (P _{max} = 161W) |
| Power Factor THD: | ≥0.95 <10 % (At full load) |
| Expected life (Ta=77°F 25°C): | > 100.000 h L90B10 @ LED 700mA |
| Operational temperature (Ta): | T _{min} = -40°F (-40°C) T _{max} = 131°F (55°C) 101,5W 122°F (50°C) 146W |
| Storage temperature: | -40°F/+176°F (-40°C/+80°C) |
| Overcharge protection: | Main surge immunity up to 10kV |
| Standard functions: | Current fixed Virtual midnight 1-10V CLO |

Materials

| | |
|-------------------|---|
| Lighting fixture: | Powder coated Die cast aluminium EN1706 |
| Optical system: | Aluminum reflector with silver PVD treatment, purity 99.7% oxidized and polished. |
| Screen: | Screen-printed ultraclear tempered glass Th. 0,15in (4mm) |
| Fixing plate: | Galvanized steel S235 |
| Gaskets: | Removable silicon |
| Cable gland: | Polyamide PA66 PG16 Ø 0,55in (14mm) MAX |
| Screws and bolts: | AISI 304 stainless steel |
| Fixture color: | RAL 9005 |

LED FEATURES


| | |
|---------------------------|---|
| LED data 4.000 K - 700mA: | 340 lm/LED 180 lm/W 77°F (25°C) [Tj] ≤ 3 step MacAdam |
| Color temperature: | 3.000 K 4.000 K 5.700 K CRI ≥ 70 |

OPTIONAL

| | |
|------------------------------------|--|
| Additional surge protector device: | SPD Max peak current 10kV/kA 8/20µs |
| Electrical optional: | 1,64ft (0,5m) power cable with 2-3 or 4-5 core connector |
| Optional functions: | DALI-DALI2 |


ASYMMETRICAL DISTRIBUTION \\\

R1A




SYMMETRICAL DISTRIBUTION \\\


R2A




R2B




R3A



R3B




R3C




FLOODLIGHT DISTRIBUTION \\\


R9A



R9B



R10A





R2B



R3A



The LED modules nominal data refers only to the LED light sources in a standard version, with 4000 K color temperature, color rendering index CRI 70 min. and a junction temperature t_j of 77°F (25°C). The LED nominal data are extrapolated from the manufacturer documentations.

| LED code | | (*) I [mA] | Luminous flux [lm] | Power [W] | Efficiency [lm/W] |
|----------|---|---------------|--------------------|-----------|-------------------|
| RF09 |  | 350 | 6934 | 35,3 | 196 |
| | | 525 | 9839 | 54,1 | 182 |
| | | 700 | 12360 | 73,2 | 169 |
| | | 1050 | 16868 | 112,8 | 150 |
| RF12 |  | 350 | 9246 | 47,1 | 196 |
| | | 525 | 12867 | 71,8 | 179 |
| | | 700 | 16157 | 97,1 | 166 |
| | | 1050 | 22037 | 149,5 | 147 |

The lighting fixture measured data refers to GMR ENLIGHTS products in a standard version, with 4000 K color temperature, optica type R3A and an ambient temperature t_a of 77°F(25 °C).

GMR ENLIGHTS offers the possibility of driving the device with custom currents (*).

Feature availability is subject to configurations. To obtain luminous fluxes and efficiencies of the lighting fixture in case of optic type and/or color temperature and/or color rendering index different from the standard use the conversion factors shown in the tables.

| | | (*) I [mA] | Luminous flux [lm] | Power [W] | Efficiency [lm/W] |
|------|---|---------------|--------------------|-----------|-------------------|
| RF09 |  | 350 | 6516 | 40,0 | 163 |
| | | 525 | 9246 | 61,5 | 150 |
| | | 700 | 11616 | 83,0 | 140 |
| | | 1050 | 15852 | 124,0 | 128 |
| RF12 |  | 350 | 8689 | 53,0 | 164 |
| | | 525 | 12092 | 80,5 | 150 |
| | | 700 | 15183 | 109,0 | 139 |
| | | 1050 | 20710 | 161,5 | 128 |

OPTIC CONVERSION FACTOR LUMINOUS FLUX

| Optic type | Flux multiplier |
|------------|-----------------|
| R2A | 0,99 |
| R2B | 0,98 |
| R3B R3C | 1,00 |
| R9A | 1,00 |
| R9B | 0,98 |
| R10A | 0,99 |

Tk CONVERSION FACTOR LUMINOUS FLUX

| Tk [K] | Flux multiplier |
|--------|-----------------|
| 3.000 | 0,94 |
| 5.700 | 1,01 |

CRI CONVERSION FACTOR LUMINOUS FLUX

| CRI (color render index) | Flux multiplier |
|--------------------------|-----------------|
| 70 | 1,00 |
| 80 | 0,93 |

(*) See pag: Available optical system, to check the optic type availability.

(**) See pag: Technical data, to check the colour temperature availability.

Functions

Standard functionality

Fixed current

During production, the light fixture is pre-set with a fixed current amongst the standard settings that appear in the tables on page 3. Upon customer's request, it is also possible to set a specific current (custom setting).

Virtual Midnight | Automatic dimming

The driver is programmed to automatically dim the light output according to the time. As required by regulations, the maximum output is set during initial hours and towards the end of the light fixture's operating time interval. During these hours there is statistically more traffic. The light output is then dimmed during the central hours of the operating time interval. This management is achievable through a self-learning process of the device, that establishes the centre point of the time interval. This moment is called "virtual midnight" and it is the point that the dimming profile refers to in order to know when to reduce the light output. We can manage up to 8hrs of programming that evolve around the virtual midnight and up to 5 steps of dimming. This way the light output will adjust automatically, adapting throughout the year to the duration of the nighttime, by referring to the pre-set parameters based on the centre point of the operating time interval.


CLO Constant Lumen Output

LEDs over time are inevitably subject to performance depreciation. This light reduction may be compensated by gradually increasing the LED's current during its lifespan, this corresponds to a gradual increase of lumen output proportional to the amount that is naturally depreciated.


On request functionality

DALI - DALI2 Control and monitoring system

On request, the fixture can be fitted with a DALI2 communication interface. This protocol allows it to be monitored and controlled remotely through use of Dali control buses.



Example of 4-step adjustment with virtual midnight



CLO Light Flow Compensation

Protection cycles

GMR ENLIGHTS works with cast iron, steel and aluminum. The materials are selected and processed to maximize performance and quality.

GALVANIZED STEEL

Protection of galvanized steel surfaces for poles

The protection of galvanized steel elements is achieved by following steps:

- Micro sandblasting;
- First epoxy layer application followed by: Wilting > Drying > Cooling;
- Acrylic glaze layer application followed by: Wilting > Drying > Cooling;
- Packing at least after 24-hour-drying at room temperature.

Protection of galvanized steel surfaces for brackets and pastorals

The protection of the galvanized steel elements is achieved thanks to:

- Micro sandblasting;
- Phosphoric pickling bath at a ph level ranging from 1.5 to 3;
- Rinsing with demineralised water;
- First powder layer application;
- Kiln firing;
- Application of a final powder layer;
- Kiln roasting of the final powder layer at 180°C (356°F);
- Cooling.

CAST IRON

Protection of cast iron surfaces for bases

The protection of cast iron elements is achieved by the following treatments:

- Surface micro shotblasting;
- Mono-component dip galvanizing followed by: Wilting > Drying > Cooling;
- Epoxy micaceous primer application followed by: Wilting > Drying > Cooling;
- Acrylic enamel application followed by: Wilting > Drying > Cooling;
- Packing at least after 24-hour-drying at room temperature.

DIE-CAST ALUMINIUM

Protection of die-cast aluminium surfaces for lighting fixtures, tops, collars, brackets and pastorals

Lighting fixtures, brackets, pastoral, and die-cast accessories undergo a cycle of powder painting which creates a barrier against the corrosion of metal parts. Moreover this barrier makes the finished product comply with design specifications in terms of surface roughness, color and reflectance.

The cycle consists of the following steps:

- Micro sandblasting;
- Hot pickling bath in a zinc-based phosphodegreasing solution;
- Specific process for the preparation of surfaces before painting;
- Washing with water;
- Rinsing with demineralised water and subsequent drying;
- First powder layer application followed by kiln baking at 180°C (356°F);
- Final powder layer application using a High Durability product and final kiln roasting at 180°C (356°F).



Salt spray test

The top quality of such treatments is confirmed by salt spray tests performed in accordance with standard ISO 9227:2017 Neutral Salt Spray test (NSS).

The test was carried out for 8.000 hours at 35°C (95°F) and demonstrated through the report test released.



GMR ENLIGHTS s.r.l.

Legal headquarters:
Strada Provinciale Specchia - Alessano, 68 • 73040 (LE)

Administrative and operational headquarters:
Via Grande n°226 • 47032 Bertinoro (FC)

T +39 0543 462611
F +39 0543 449111

sales@gmrenlights.com
www.gmrenlights.com